



Mahatma Gandhi Vidyamandir's
Panchavati College of Management & Computer Science



E - Content

Department of BBA/BBA(CA)

Advance PHP

SYBBA(CA)

Prof. Kushal Vilasrao Deshmukh
MGV's PCMCS Nashik-03

Table of Contents

About the Tutorial	i
Audience	i
Prerequisites	i
Copyright & Disclaimer	i
Table of Contents	ii
PART 1: LEARNING PHP	1
1. PHP – Introduction	2
Common Uses of PHP	2
Characteristics of PHP	3
"Hello World" Script in PHP	3
2. PHP – Environment Setup	4
PHP Parser Installation	4
PHP Installation on Linux or Unix with Apache	4
PHP Installation on Mac OS X with Apache	6
PHP Installation on Windows NT/2000/XP with IIS	7
PHP Installation on Windows NT/2000/XP with Apache	8
Apache Configuration for PHP	10
PHP.INI file Configuration	11
3. PHP – Syntax Overview	15
Escaping to PHP	15
Commenting PHP Code	16
PHP is whitespace insensitive	16
PHP is case sensitive	17
Statements are expressions terminated by semicolons	17
Expressions are combinations of tokens	17
Braces make blocks	17
Running PHP Script from Command Prompt	18
4. PHP – Variable Types	19
Integers	20
Doubles	20
Boolean	20
NULL	21
Strings	21
Variable Naming	24

	PHP
PHP – Variables	24
PHP Local Variables.....	24
PHP Function Parameters.....	25
PHP Global Variables.....	25
PHP Static Variables	26
5. PHP – Constants	27
6. PHP – Operator Types	29
Arithmetic Operators.....	29
Comparison Operators	31
Logical Operators	33
Assignment Operators.....	35
Conditional Operator	37
Operators Categories	38
Precedence of PHP Operators	38
7. PHP – Decision Making	40
The If...Else Statement	40
The Elself Statement	41
The Switch Statement.....	42
8. PHP – Loop Types.....	45
The for loop statement.....	45
The while loop statement.....	46
The do...while loop statement.....	47
The foreach loop statement.....	48
The break statement.....	48
The continue statement	50
9. PHP – Arrays	52
Numeric Array.....	52
Associative Arrays	53
Multidimensional Arrays	54
10. PHP – Strings	57
String Concatenation Operator.....	58
Using the strlen() function.....	58
Using the strpos() function.....	59
11. PHP – Web Concepts.....	60
Identifying Browser & Platform	60
Display Images Randomly	61
Using HTML Forms.....	62
Browser Redirection	63
Displaying "File Download" Dialog Box	64
12. PHP – GET and POST Methods	66
The GET Method	66
The POST Method.....	67
The \$_REQUEST variable	68
13. PHP – File Inclusion	70
The include() Function	70
The require() Function	71
14. PHP – Files & I/O	72

	PHP
Opening and Closing Files	72
Reading a file	73
Writing a File	74
15. PHP – Functions	76
Creating PHP Function	76
PHP Functions with Parameters	77
Passing Arguments by Reference	77
PHP Functions returning value	78
Setting Default Values for Function Parameters	79
Dynamic Function Calls	80
16. PHP – Cookies	81
The Anatomy of a Cookie	81
Setting Cookies with PHP	82
Accessing Cookies with PHP	83
Deleting Cookie with PHP	84
17. PHP – Sessions	85
Starting a PHP Session	85
Destroying a PHP Session	87
Turning on Auto Session	87
Sessions without cookies	87
18. PHP – Sending Emails	89
Sending plain text email	89
Sending HTML email	91
Sending attachments with email	92
19. PHP – File Uploading	95
Creating an Upload Form	95
Creating an upload script	96
20. PHP – Coding Standard	98
PART 2: ADVANCED PHP	101
21. PHP – Predefined Variables	102
PHP Superglobals	102
Server variables: \$_SERVER	103
22. PHP – Regular Expression	106
POSIX Regular Expressions	106
PHP's Regexp POSIX Functions	108
PHP – Function ereg()	108
PHP – Function ereg_replace()	110
PHP – Function eregi()	111
PHP – Function eregi_replace()	112
PHP – Function split()	113
PHP – Function spliti()	114
PHP – Function sql_regcase()	115
PERL Style Regular Expressions	115
PHP's Regexp PERL Compatible Functions	117
PHP – Function preg_match()	117
PHP – Function preg_match_all()	118
PHP – Function preg_replace()	119

	PHP
PHP – Function preg_split()	120
PHP – Function preg_grep()	121
PHP – Function preg_quote()	122
23. PHP – Error and Exception Handling.....	124
Using die() function.....	124
Defining Custom Error Handling Function	124
Exceptions Handling.....	127
24. PHP – Bugs Debugging	129
25. PHP – Date and Time	131
Getting the Time Stamp with time()	131
Converting a Time Stamp with getdate()	131
Converting a Time Stamp with date()	133
26. PHP – PHP and MySQL.....	136
What you should already have?	136
Connecting to MySQL Database	137
Create MySQL Database Using PHP.....	138
Delete MySQL Database Using PHP	143
Insert Data to MySQL Database.....	144
Retrieving Data from MySQL Database	148
Using Paging through PHP.....	152
Updating Data into MySQL Database	154
Deleting Data from MySQL Database	157
Using PHP to Backup MySQL Database	159
27. PHP – PHP and AJAX	162
What is AJAX ?.....	162
PHP and AJAX Example	162
Client Side HTML file.....	163
Server Side PHP file.....	165
28. PHP – PHP and XML	167
HTML list that's not valid XML	167
HTML list that is valid XML	167
Parsing an XML Document.....	167
Generating an XML Document	169
29. PHP – Object Oriented Programming	170
Object Oriented Concepts	170
Defining PHP Classes	171
Creating Objects in PHP.....	172
Calling Member Functions.....	172
Constructor Functions	173
Destructor	174
Inheritance	174
Function Overriding	175
Public Members	175
Private members.....	175
Protected members	176
Interfaces	177
Constants.....	177
Abstract Classes.....	177
Static Keyword.....	178

Final Keyword	PHP
Final Keyword	178
30. PHP – PHP for C Developers	181
Similarities	181
Differences.....	181
31. PHP – PHP for PERL Developers	183
Similarities	183
Differences.....	183
PART 3: FUNCTION REFERENCE	185
32. PHP – Function Reference	186

Part 1: Learning PHP

1. PHP – INTRODUCTION

PHP started out as a small open source project that evolved as more and more people found out how useful it was. Rasmus Lerdorf unleashed the first version of PHP way back in 1994.

- PHP is a recursive acronym for "PHP: Hypertext Preprocessor".
- PHP is a server side scripting language that is embedded in HTML. It is used to manage dynamic content, databases, session tracking, even build entire e-commerce sites.
- It is integrated with a number of popular databases, including MySQL, PostgreSQL, Oracle, Sybase, Informix, and Microsoft SQL Server.
- PHP is pleasingly zippy in its execution, especially when compiled as an Apache module on the Unix side. The MySQL server, once started, executes even very complex queries with huge result sets in record-setting time.
- PHP supports a large number of major protocols such as POP3, IMAP, and LDAP. PHP4 added support for Java and distributed object architectures (COM and CORBA), making n-tier development a possibility for the first time.
- PHP is forgiving: PHP language tries to be as forgiving as possible.
- PHP Syntax is C-Like.

Common Uses of PHP

PHP performs system functions, i.e. from files on a system it can create, open, read, write, and close them. The other uses of PHP are:

- PHP can handle forms, i.e. gather data from files, save data to a file, thru email you can send data, return data to the user.
 - You add, delete, modify elements within your database thru PHP.
 - Access cookies variables and set cookies.
 - Using PHP, you can restrict users to access some pages of your website.
 - It can encrypt data.
-

Characteristics of PHP

Five important characteristics make PHP's practical nature possible:

- Simplicity
- Efficiency
- Security
- Flexibility
- Familiarity

"Hello World" Script in PHP

To get a feel of PHP, first start with simple PHP scripts. Since "Hello, World!" is an essential example, first we will create a friendly little "Hello, World!" script.

As mentioned earlier, PHP is embedded in HTML. That means that in amongst your normal HTML (or XHTML if you're cutting-edge) you'll have PHP statements like this:

```
<html>
<head>
<title>Hello World</title>
<body>
  <?php echo "Hello, World!";?>
</body>
</html>
```

It will produce the following result:

```
Hello, World!
```

If you examine the HTML output of the above example, you'll notice that the PHP code is not present in the file sent from the server to your Web browser. All of the PHP present in the Web page is processed and stripped from the page; the only thing returned to the client from the Web server is pure HTML output.

All PHP code must be included inside one of the three special markup tags that are recognized by the PHP Parser.

```
<?php PHP code goes here ?>

<? PHP code goes here ?>

<script language="php"> PHP code goes here </script>
```

Most common tag is the <?php...?> and we will also use the same tag in our tutorial.

From the next chapter, we will start with PHP Environment Setup on your machine and then we will dig out almost all concepts related to PHP to make you comfortable with the PHP language.

2.PHP—ENVIRONMENT SETUP

In order to develop and run PHP Web pages, three vital components need to be installed on your computer system.

Web Server - PHP will work with virtually all **Web Server** software, including Microsoft's Internet Information Server (IIS) but then most often used is freely available Apache Server. Download Apache for free here: <http://httpd.apache.org/download.cgi>

Database - PHP will work with virtually all database software, including Oracle and Sybase but most commonly used is freely available MySQL database. Download MySQL for free here: <http://www.mysql.com/downloads/index.html>

PHP Parser - In order to process PHP script instructions, a parser must be installed to generate HTML output that can be sent to the **Web Browser**. This tutorial will guide you how to install PHP parser on your computer.

PHP Parser Instal ation

Before you proceed, it is important to make sure that you have a proper environment setup on your machine to develop your web programs using PHP.

Type the following address into your browser's address box.

`http://127.0.0.1/info.php`

If this displays a page showing your PHP installation related information, then it means you have PHP and Webserver installed properly. Otherwise you have to follow given procedure to install PHP on your computer.

This section will guide you to install and configure PHP over the following four platforms:

- [PHP Installation on Linux or Unix with Apache](#)
- [PHP Installation on Mac OS X with Apache](#)
- [PHP Installation on Windows NT/2000/XP with IIS](#)
- [PHP Installation on Windows NT/2000/XP with Apache](#)

PHP Instal ation on Linux or Unix with Apache

If you plan to install PHP on Linux or any other variant of Unix, then here is the list of prerequisites:

- The PHP source distribution <http://www.php.net/downloads.php>
The latest Apache source distribution
<http://httpd.apache.org/download.cgi>
- A working PHP-supported database, if you plan to use one (For example MySQL, Oracle etc.)
- Any other supported software to which PHP must connect (mail server, BCMath package, JDK, and so forth)
- An ANSI C compiler
- Gnu make utility - you can freely download it at
<http://www.gnu.org/software/make>

Now here are the steps to install Apache and PHP5 on your Linux or Unix machine. If your PHP or Apache versions are different, then please take care accordingly.

-
- If you haven't already done so, unzip and untar your Apache source distribution. Unless you have a reason to do otherwise, /usr/local is the standard place.

```
gunzip -c apache_1.3.x.tar.gz
tar -xvf apache_1.3.x.tar
```

- Build the apache Server as follows

```
cd apache_1.3.x
./configure --prefix=/usr/local/apache --enable-so
make
make install
```

- Unzip and untar your PHP source distribution. Unless you have a reason to do otherwise, /usr/local is the standard place.

```
gunzip -c php-5.x.tar.gz
tar -xvf php-5.x.tar
cd php-5.x
```

- Configure and Build your PHP, assuming you are using MySQL database.

```
./configure --with-apxs=/usr/sbin/apxs \
            --with-mysql=/usr/bin/mysql
make
make install
```

- Install the php.ini file. Edit this file to get configuration directives:

```
cd ../../php-5.x
cp php.ini-dist /usr/local/lib/php.ini
```

- Tell your Apache server where you want to serve files from, and what extension(s) you want to identify PHP files. **.php** is the standard, but you can use `.html`, `.phtml`, or whatever you want.
 - Go to your HTTP configuration files (`/usr/local/apache/conf` or whatever your path is)
 - Open `httpd.conf` with a text editor.
 - Search for the word `DocumentRoot` (which should appear twice), and change both paths to the directory you want to serve files out of (in our case, `/home/httpd`). We recommend a home directory rather than the default `/usr/local/apache/htdocs` because it is more secure, but it doesn't have to be in a home directory. You will keep all your PHP files in this directory.
- Add at least one PHP extension directive, as shown in the first line of code that follows. In the second line, we've also added a second handler to have all HTML files parsed as PHP

```
AddType application/x-httpd-php .php
AddType application/x-httpd-php .html
```

- Restart your server. Every time you change your HTTP configuration or `php.ini` files, you must stop and start your server again.

```
cd ../bin
./apachectl start
```

- Set the document root directory permissions to world-executable. The actual PHP files in the directory need only be world-readable (644). If necessary, replace `/home/httpd` with your document root below:

```
chmod 755 /home/httpd/html/php
```

- Open a text editor. Type: `<?php phpinfo(); ?>`. Save this file in your Web server's document root as `info.php`.
- Start any Web browser and browse the file. You must always use an HTTP request (`http://www.testdomain.com/info.php` or `http://localhost/info.php` or `http://127.0.0.1/info.php`) rather than a filename (`/home/httpd/info.php`) for the file to be parsed correctly

You should see a long table of information about your new PHP installation message
Congratulations!

PHP Installation on Mac OS X with Apache

Mac users have the choice of either a binary or a source installation. In fact, your OS X probably came with Apache and PHP preinstalled. This is likely to be quite an old build, and it probably lacks many of the less common extensions.

However, if all you want is a quick Apache + PHP + MySQL/PostgreSQL setup on your laptop, this is certainly the easiest way to fly. All you need to do is edit your Apache configuration file and turn on the Web server.

So just follow the steps given below:

- Open the Apache config file in a text editor as root.

```
sudo open -a TextEdit /etc/httpd/httpd.conf
```

- Edit the file. Uncomment the following lines:

```
LoadModule php5_module
AddModule mod_php5.c
AddType application/x-httpd-php .php
```

- You may also want to uncomment the <Directory /home/*/Sites> block or otherwise tell Apache which directory to serve out of.
- Restart the Web server

```
sudo apachectl graceful
```

- Open a text editor. Type: <?php phpinfo(); ?>. Save this file in your Web server's document root as info.php.
-
- Start any Web browser and browse the file. you must always use an HTTP request (http://www.testdomain.com/info.php or http://localhost/info.php or http://127.0.0.1/info.php) rather than a filename (/home/httpd/info.php) for the file to be parsed correctly

You should see a long table of information about your new PHP installation message
Congratulations!

PHP Installation on Windows NT/2000/XP with IIS

The Windows server installation of PHP running IIS is much simpler than on Unix, since it involves a precompiled binary rather than a source build.

If you plan to install PHP over Windows, then here is the list of prerequisites:

- A working PHP-supported Web server. Under previous versions of PHP, IIS/PWS was the easiest choice because a module version of PHP was available for it; but PHP now has added a much wider selection of modules for Windows.
- A correctly installed PHP-supported database like MySQL or Oracle etc. (if you plan to use one)
- The PHP Windows binary distribution (download it at www.php.net/downloads.php)
- A utility to unzip files (search <http://download.cnet.com> for PC file compression utilities)

Now here are the steps to install Apache and PHP5 on your Windows machine. If your PHP version is different, then please take care accordingly.

-
- Extract the binary archive using your unzip utility; C:\PHP is a common location.
- Copy some .dll files from your PHP directory to your systems directory (usually C:\Winnt\System32). You need php5ts.dll for every case. You will also probably need to copy the file corresponding to your Web server module - C:\PHP\Sapi\php5isapi.dll. It's possible you will also need others from the dlls subfolder - but start with the two mentioned above and add more if you need them.
- Copy either php.ini-dist or php.ini-recommended (preferably the latter) to your Windows directory (C:\Winnt or C:\Winnt40), and rename it php.ini. Open this file in a text editor (for example, Notepad). Edit this file to get configuration directives; We highly recommend new users set error reporting to E_ALL on their development machines at this point. For now, the most important thing is the doc_root directive under the Paths and Directories section. make sure this matches your IIS Inetpub folder (or wherever you plan to serve out of).
- Stop and restart the WWW service. Go to the Start menu -> Settings -> Control Panel -> Services. Scroll down the list to IIS Admin Service. Select it and click Stop. After it stops, select World Wide Web Publishing Service and click Start. Stopping and restarting the service from within Internet Service Manager will not suffice. Since this is Windows, you may also wish to reboot.
- Open a text editor. Type: `<?php phpinfo(); ?>`. Save this file in your Web server's document root as info.php.
- Start any Web browser and browse the file. you must always use an HTTP request (<http://www.testdomain.com/info.php> or <http://localhost/info.php> or <http://127.0.0.1/info.php>) rather than a filename (`/home/httpd/info.php`) for the file to be parsed correctly

You should see a long table of information about your new PHP installation message
Congratulations!

PHP Installation on Windows NT/2000/XP with Apache

To install Apache with PHP 5 on Windows follow the following steps. If your PHP and Apache versions are different, then please take care accordingly.

- Download Apache server from www.apache.org/dist/httpd/binaries/win32. You want the current stable release version with the `no_src.msi` extension. Double-click the installer file to install; `C:\Program Files` is a common location. The installer will also ask you whether you want to run Apache as a service or from the command line or DOS prompt. We recommend you do not install as a service, as this may cause problems with startup.
- Extract the PHP binary archive using your unzip utility; `C:\PHP` is a common location.
- Copy some `.dll` files from your PHP directory to your system directory (usually `C:\Windows`). You need `php5ts.dll` for every case. You will also probably need to copy the file corresponding to your Web server module - `C:\PHP\Sapi\php5apache.dll`. to your Apache modules directory. It's possible that you will also need others from the `dlls` subfolder, but start with the two mentioned previously and add more if you need them.
- Copy either `php.ini-dist` or `php.ini-recommended` (preferably the latter) to your Windows directory, and rename it `php.ini`. Open this file in a text editor (for example, Notepad). Edit this file to get configuration directives; At this point, we highly recommend that new users set error reporting to `E_ALL` on their development machines.
- Tell your Apache server where you want to serve files from and what extension(s) you want to identify PHP files (`.php` is the standard, but you can use `.html`, `.phtml`, or whatever you want). Go to your HTTP configuration files (`C:\Program Files\Apache Group\Apache\conf` or whatever your path is), and open `httpd.conf` with a text editor. Search for the word `DocumentRoot` (which should appear twice) and change both paths to the directory you want to serve files out of. (The default is `C:\Program Files\Apache Group\Apache\htdocs`.) Add at least one PHP extension directive as shown in the first line of the following code:

```
LoadModule php5_module modules/php5apache.dll
AddType application/x-httpd-php .php .phtml
```

-
- You may also need to add the following line:

```
AddModule mod_php5.c
```

- Stop and restart the WWW service. Go to the Start menu -> Settings -> Control Panel -> Services. Scroll down the list to IIS Admin Service. Select it and click Stop. After it stops, select World Wide Web Publishing Service and click Start. Stopping and restarting the service from within Internet Service Manager will not suffice. Since this is Windows, you may also wish to reboot.

- Open a text editor. Type: `<?php phpinfo(); ?>`. Save this file in your Web server's document root as `info.php`.
- Start any Web browser and browse the file. you must always use an HTTP request (`http://www.testdomain.com/info.php` or `http://localhost/info.php` or `http://127.0.0.1/info.php`) rather than a filename (`/home/httpd/info.php`) for the file to be parsed correctly

You should see a long table of information about your new PHP installation message
Congratulations!

Apache Configuration

If you are using Apache as a Web Server, then this section will guide you to edit Apache Configuration Files.

PHP.INI File Configuration

The PHP configuration file, `php.ini`, is the final and most immediate way to affect PHP's functionality.

Just Check it here: [PHP.INI File Configuration](#)

Windows IIS Configuration

To configure IIS on your Windows machine you can refer your IIS Reference Manual shipped along with IIS.

Apache Configuration for PHP

Apache uses `httpd.conf` file for global settings, and the `.htaccess` file for per-directory access settings. Older versions of Apache split up `httpd.conf` into three files (`access.conf`, `httpd.conf`, and `srm.conf`), and some users still prefer this arrangement.

Apache server has a very powerful, but slightly complex, configuration system of its own. Learn more about it at the Apache Web site: www.apache.org

The following section describes settings in `httpd.conf` that affect PHP directly and cannot be set elsewhere. If you have standard installation, then `httpd.conf` will be found at `/etc/httpd/conf`:

Timeout

This value sets the default number of seconds before any HTTP request will time out. If you set PHP's `max_execution_time` to longer than this value, PHP will keep grinding away but the

user may see a 404 error. In safe mode, this value will be ignored; you must use the timeout value in php.ini instead

DocumentRoot

DocumentRoot designates the root directory for all HTTP processes on that server. It looks something like this on Unix:

```
DocumentRoot ./usr/local/apache_1.3.6/htdocs.
```

You can choose any directory as document root.

AddType

The PHP MIME type needs to be set here for PHP files to be parsed. Remember that you can associate any file extension with PHP like .php3, .php5 or .htm.

```
AddType application/x-httpd-php .php
AddType application/x-httpd-phps .phps
AddType application/x-httpd-php3 .php3 .html
AddType application/x-httpd-php .html
```

Action

You must uncomment this line for the Windows apxs module version of Apache with shared object support:

```
LoadModule php4_module modules/php4apache.dll
```

or on Unix flavors:

```
LoadModule php4_module modules/mod_php.so
```

AddModule

You must uncomment this line for the static module version of Apache.

```
AddModule mod_php4.c
```

PHP.INI file Configuration

The PHP configuration file, php.ini, is the final and most immediate way to affect PHP's functionality. The php.ini file is read each time PHP is initialized. In other words, whenever httpd is restarted for the module version or with each script execution for the CGI version. If

your change isn't showing up, remember to stop and restart httpd. If it still isn't showing up, use `phpinfo()` to check the path to `php.ini`.

The configuration file is well commented and thorough. Keys are case sensitive, keyword values are not; whitespace, and lines beginning with semicolons are ignored. Booleans can be represented by 1/0, Yes/No, On/Off, or True/False. The default values in `php.ini-dist` will result in a reasonable PHP installation that can be tweaked later.

Here we are explaining the important settings in `php.ini` which you may need for your PHP Parser.

short_open_tag = Off

Short open tags look like this: `<? ?>`. This option must be set to Off if you want to use XML functions.

safe_mode = Off

If this is set to On, you probably compiled PHP with the `--enable-safe-mode` flag. Safe mode is most relevant to CGI use. See the explanation in the section "CGI compile-time options" earlier in this chapter.

safe_mode_exec_dir = [DIR]

This option is relevant only if safe mode is on; it can also be set with the `--with-exec-dir` flag during the Unix build process. PHP in safe mode only executes external binaries out of this directory. The default is `/usr/local/bin`. This has nothing to do with serving up a normal PHP/HTML Web page.

safe_mode_allowed_env_vars = [PHP_]

This option sets which environment variables users can change in safe mode. The default is only those variables prepended with "PHP_". If this directive is empty, most variables are alterable.

safe_mode_protected_env_vars = [LD_LIBRARY_PATH]

This option sets which environment variables users can't change in safe mode, even if `safe_mode_allowed_env_vars` is set permissively.

disable_functions = [function1, function2...]

A welcome addition to PHP4 configuration and one perpetuated in PHP5 is the ability to disable selected functions for security reasons. Previously, this necessitated hand-editing the C code from which PHP was made. Filesystem, system, and network functions should probably be the first to go because allowing the capability to write files and alter the system over HTTP is never such a safe idea.

max_execution_time = 30

The function `set_time_limit()` won't work in safe mode, so this is the main way to make a script time out in safe mode. In Windows, you have to abort based on maximum memory consumed rather than time. You can also use the Apache timeout setting to timeout if you use Apache, but that will apply to non-PHP files on the site too.

error_reporting = E_ALL & ~E_NOTICE

The default value is `E_ALL & ~E_NOTICE`, all errors except notices. Development servers should be set to at least the default; only production servers should even consider a lesser value

error_prepend_string = [""]

With its bookend, `error_append_string`, this setting allows you to make error messages a different color than other text, or what you have.

warn_plus_overloading = Off

This setting issues a warning if the `+` operator is used with strings, as in a form value.

variables_order = EGPCS

This configuration setting supersedes `gpc_order`. Both are now deprecated along with `register_globals`. It sets the order of the different variables: Environment, GET, POST, COOKIE, and SERVER (aka Built-in).

You can change this order around. Variables will be overwritten successively in left-to-right order, with the rightmost one winning the hand every time. This means if you left the default setting and happened to use the same name for an environment variable, a POST variable, and a COOKIE variable, the COOKIE variable would own that name at the end of the process. In real life, this doesn't happen much.

register_globals = Off

This setting allows you to decide whether you wish to register EGPCS variables as global. This is now deprecated, and as of PHP4.2, this flag is set to Off by default. Use superglobal arrays instead. All the major code listings in this book use superglobal arrays.

gpc_order = GPC

This setting has been GPC Deprecated.

magic_quotes_gpc = On

This setting escapes quotes in incoming GET/POST/COOKIE data. If you use a lot of forms which possibly submit to themselves or other forms and display form values, you may need to set this directive to On or prepare to use addslashes() on string-type data.

magic_quotes_runtime = Off

This setting escapes quotes in incoming database and text strings. Remember that SQL adds slashes to single quotes and apostrophes when storing strings and does not strip them off when returning them. If this setting is Off, you will need to use stripslashes() when outputting any type of string data from a SQL database. If magic_quotes_sybase is set to On, this must be Off.

magic_quotes_sybase = Off

This setting escapes single quotes in incoming database and text strings with Sybase-style single quotes rather than backslashes. If magic_quotes_runtime is set to On, this must be Off.

auto-prepend-file = [path/to/file]

If a path is specified here, PHP must automatically include() it at the beginning of every PHP file. Include path restrictions do apply.

auto-append-file = [path/to/file]

If a path is specified here, PHP must automatically include() it at the end of every PHP file. unless you escape by using the exit() function. Include path restrictions do apply.

include_path = [DIR]

If you set this value, you will only be allowed to include or require files from these directories. The include directory is generally under your document root; this is mandatory if you're running in safe mode. Set this to . in order to include files from the same directory your script is in. Multiple directories are separated by colons: ./usr/local/apache/htdocs:/usr/local/lib.

doc_root = [DIR]

If you're using Apache, you've already set a document root for this server or virtual host in httpd.conf. Set this value here if you're using safe mode or if you want to enable PHP only on a portion of your site (for example, only in one subdirectory of your Web root).

file_uploads = [on/off]

Turn on this flag if you will upload files using PHP script.

upload_tmp_dir = [DIR]

Do not uncomment this line unless you understand the implications of HTTP uploads!

session.save-handler = files

Except in rare circumstances, you will not want to change this setting. So don't touch it.

ignore_user_abort = [On/Off]

This setting controls what happens if a site visitor clicks the browser's Stop button. The default is On, which means that the script continues to run to completion or timeout. If the setting is changed to Off, the script will abort. This setting only works in module mode, not CGI.

mysql.default_host = hostname

The default server host to use when connecting to the database server if no other host is specified.

mysql.default_user = username

The default user name to use when connecting to the database server if no other name is specified.

mysql.default_password = password

The default password to use when connecting to the database server if no other password is specified.

3.PHP—SYNTAX OVERVIEW

Escaping to PHP

The PHP parsing engine needs a way to differentiate PHP code from other elements in the page. The mechanism for doing so is known as 'escaping to PHP.' There are four ways to do this:

Canonical PHP tags

The most universally effective PHP tag style is:

```
<?php...?>
```

If you use this style, you can be positive that your tags will always be correctly interpreted.

Short-open (SGML-style) tags

Short or short-open tags look like this:

```
<?...?>
```

Short tags are, as one might expect, the shortest **option You must** do one of two things to enable PHP to recognize the tags:

- Choose the `--enable-short-tags` configuration option when you're building PHP.
- Set the `short_open_tag` setting in your `php.ini` file to `on`. This option must be disabled to parse XML with PHP because the same syntax is used for XML tags.

ASP-style tags

ASP-style tags mimic the tags used by Active Server Pages to delineate code blocks. ASP-style tags look like this:

```
<%...%>
```

To use ASP-style tags, you will need to set the configuration option in your `php.ini` file.

HTML script tags

HTML script tags look like this:

```
<script language="PHP">...</script>
```

Commenting PHP Code

A *comment* is the portion of a program that exists only for the human reader and stripped out before displaying the programs result. There are two commenting formats in PHP:

Single-line comments: They are generally used for short explanations or notes relevant to the local code. Here are the examples of single line comments.

```
<?
# This is a comment, and
# This is the second line of the comment
// This is a comment too. Each style comments only
print "An example with single line comments";
?>
```

Multi-lines printing: Here are the examples to print multiple lines in a single print statement:

```
<?
# First Example
print <<<END
This uses the "here document" syntax to output
multiple lines with $variable interpolation. Note
that the here document terminator must appear on a
line with just a semicolon no extra whitespace!
END;
# Second Example
print "This spans
multiple lines. The newlines will be
output as well";
?>
```

Multi-lines comments: They are generally used to provide pseudocode algorithms and more detailed explanations when necessary. The multiline style of commenting is the same as in C. Here are the example of multi lines comments.

```
<?
/* This is a comment with multiline
   Author : Mohammad Mohtashim
   Purpose: Multiline Comments Demo
   Subject: PHP
*/
print "An example with multi line comments";
?>
```


PHP is whitespace insensitive

Whitespace is the stuff you type that is typically invisible on the screen, including spaces, tabs, and carriage returns (end-of-line characters).

PHP whitespace insensitive means that it almost never matters how many whitespace characters you have in a row. one whitespace character is the same as many such characters.

For example, each of the following PHP statements that assigns the sum of $2 + 2$ to the variable `$four` is equivalent:

```
$four = 2 + 2; // single spaces
$four <tab>=<tab>2<tab>+<tab>2 ; // spaces and tabs
$four =
2+
2; // multiple lines
```

PHP is case sensitive

Yeah it is true that PHP is a case sensitive language. Try out the following example:

```
<html>
<body>
<?
$capital = 67;
print("Variable capital is $capital<br>");
print("Variable CaPiTaL is $CaPiTaL<br>");
?>
</body>
</html>
```

This will produce the following result:

```
Variable capital is 67
Variable CaPiTaL is
```

Statements are expressions terminated by semicolons

A *statement* in PHP is any expression that is followed by a semicolon (;). Any sequence of valid PHP statements that is enclosed by the PHP tags is a valid PHP program. Here is a typical statement in PHP, which in this case assigns a string of characters to a variable called `$greeting`:

```
$greeting = "Welcome to PHP!";
```

Expressions are combinations of tokens

The smallest building blocks of PHP are the indivisible tokens, such as numbers (3.14159), strings (.two.), variables (\$two), constants (TRUE), and the special words that make up the syntax of PHP itself like if, else, while, for and so forth

Braces make blocks

Although statements cannot be combined like expressions, you can always put a sequence of statements anywhere a statement can go by enclosing them in a set of curly braces.

Here both statements are equivalent:

```
if (3 == 2 + 1)
    print("Good - I haven't totally lost my mind.<br>");

if (3 == 2 + 1)
{
    print("Good - I haven't totally");
    print("lost my mind.<br>");
}
```

Running PHP Script from Command Prompt

Yes you can run your PHP script on your command prompt. Assuming you have the following content in test.php file

```
<?php
    echo "Hello PHP!!!!!";
?>
```

Now run this script as command prompt as follows:

```
$ php test.php
```

It will produce the following result

```
Hello PHP!!!!!
```

4. PHP – VARIABLE TYPES

The main way to store information in the middle of a PHP program is by using a variable. Here are the most important things to know about variables in PHP.

- All variables in PHP are denoted with a leading dollar sign (\$).
- The value of a variable is the value of its most recent assignment.
- Variables are assigned with the = operator, with the variable on the left-hand side and the expression to be evaluated on the right.
- Variables can, but do not need, to be declared before assignment.
- Variables in PHP do not have intrinsic types - a variable does not know in advance whether it will be used to store a number or a string of characters.
- Variables used before they are assigned have default values.
- PHP does a good job of automatically converting types from one to another when necessary.
- PHP variables are Perl-like.

PHP has a total of eight data types which we use to construct our variables:

- **Integers:** are whole numbers, without a decimal point, like 4195.
- **Doubles:** are floating-point numbers, like 3.14159 or 49.1.
- **Booleans:** have only two possible values either true or false.
- **NULL:** is a special type that only has one value: NULL.
- **Strings:** are sequences of characters, like 'PHP supports string operations.'
- **Arrays:** are named and indexed collections of other values.
- **Objects:** are instances of programmer-defined classes, which can package up both other kinds of values and functions that are specific to the class.
- **Resources:** are special variables that hold references to resources external to PHP (such as database connections).

The first five are *simple types*, and the next two (arrays and objects) are compound - the compound types can package up other arbitrary values of arbitrary type, whereas the simple types cannot.

We will explain only simple data type in this chapters. Array and Objects will be explained separately.

Integers

They are whole numbers, without a decimal point, like 4195. They are the simplest type .they correspond to simple whole numbers, both positive and negative. Integers can be assigned to variables, or they can be used in expressions, like so:

```
$int_var = 12345;
$another_int = -12345 + 12345;
```

Integer can be in decimal (base 10), octal (base 8), and hexadecimal (base 16) format. Decimal format is the default, octal integers are specified with a leading 0, and hexadecimals have a leading 0x.

For most common platforms, the largest integer is $(2^{31} - 1)$ (or 2,147,483,647), and the smallest (most negative) integer is $-(2^{31} - 1)$ (or -2,147,483,647).

Doubles

They like 3.14159 or 49.1. By default, doubles print with the minimum number of decimal places needed. For example, the code:

```
$many = 2.2888800;
$many_2 = 2.2111200;
$few = $many + $many_2; print(.$many
+ $many_2 = $few<br>.);
```

It produces the following browser output:

```
2.28888 + 2.21112 = 4.5
```

Boolean

They have only two possible values either true or false. PHP provides a couple of constants especially for use as Booleans: TRUE and FALSE, which can be used like so:

```
if (TRUE)
    print("This will always print<br>");
else
    print("This will never print<br>");
```

Interpreting other types as Booleans

Here are the rules for determine the "truth" of any value not already of the Boolean type:

- If the value is a number, it is false if exactly equal to zero and true otherwise.
- If the value is a string, it is false if the string is empty (has zero characters) or is the string "0", and is true otherwise.
- Values of type NULL are always false.
- If the value is an array, it is false if it contains no other values, and it is true otherwise. For an object, containing a value means having a member variable that has been assigned a value.
- Valid resources are true (although some functions that return resources when they are successful will return FALSE when unsuccessful).
- Don't use double as Booleans.

Each of the following variables has the truth value embedded in its name when it is used in a Boolean context.

```
$true_num = 3 + 0.14159;
>true_str = "Tried and true"
>true_array[49] = "An array element";
>false_array = array();
>false_nu|| = NULL;
>false_num = 999 - 999;
>false_str = "";
```

NULL

NULL is a special type that only has one value: NULL. To give a variable the NULL value, simply assign it like this:

```
$my_var = NULL;
```

The special constant NULL is capitalized by convention, but actually it is case insensitive; you could just as well have typed:

```
$my_var = null;
```

A variable that has been assigned NULL has the following properties:

- It evaluates to FALSE in a Boolean context.
-

- It returns FALSE when tested with IsSet() function.

Strings

They are sequences of characters, like "PHP supports string operations". Following are valid examples of string:

```
$string_1 = "This is a string in double quotes";  
$string_2 = "This is a somewhat longer, singly quoted string";  
$string_39 = "This string has thirty-nine characters";  
$string_0 = ""; // a string with zero characters
```

Singly quoted strings are treated almost literally, whereas doubly quoted strings replace variables with their values as well as specially interpreting certain character sequences.

```
<?  
$variable = "name";  
$literally = 'My $variable will not print!\n';  
print($literally);  
$literally = "My $variable will print!\n";  
print($literally);  
?>
```

This will produce the following result:

```
My $variable will not print!  
My name will print
```

There are no artificial limits on string length - within the bounds of available memory, you ought to be able to make arbitrarily long strings.

Strings that are delimited by double quotes (as in "this") are preprocessed in both the following two ways by PHP:

- Certain character sequences beginning with backslash (\) are replaced with special characters
- Variable names (starting with \$) are replaced with string representations of their values.

The escape-sequence replacements are:

- \n is replaced by the newline character

- `\r` is replaced by the carriage-return character
- `\t` is replaced by the tab character
- `\$` is replaced by the dollar sign itself (`$`)
- `\"` is replaced by a single double-quote (`"`)
- `\\` is replaced by a single backslash (`\`)

Here Document

You can assign multiple lines to a single string variable using **here document**:

```
<?php

$channel =<<<_XML_
<channel>
<title>What's For Dinner<title>
<link>http://menu.example.com/<link>
<description>Choose what to eat tonight.</description>
</channel>
_XML_

echo <<<END
This uses the "here document" syntax to output
multiple lines with variable interpolation. Note
that the here document terminator must appear on a
line with just a semicolon. no extra whitespace!
<br />
END;

print $channel;
?>
```

This will produce the following result:

```
This uses the "here document" syntax to output

multiple lines with variable interpolation. Note
```

that the here document terminator must appear on a line with just a semicolon. no extra whitespace!

```
<channel>
<title>What's For Dinner<title>
<link>http://menu.example.com/<link>
<description>Choose what to eat tonight.</description>
```

Variable Naming

Rules for naming a variable is:

- Variable names must begin with a letter or underscore character.
- A variable name can consist of numbers, letters, underscores but you cannot use characters like + , - , % , (,) . & , etc

There is no size limit for variables.

PHP – Variables

Scope can be defined as the range of availability a variable has to the program in which it is declared. PHP variables can be one of four scope types:

- Local variables
- Function parameters
- Global variables
- Static variables

PHP Local Variables

A variable declared in a function is considered local; that is, it can be referenced solely in that function. Any assignment outside of that function will be considered to be an entirely different variable from the one contained in the function:

```
<?
$x = 4;
function assignx () {
```



```
$x = 0;
print "\$x inside function is $x.
";
}
assignx();
print "\$x outside of function is $x.
";
?>
```

This will produce the following result.

```
$x inside function is 0.
$x outside of function is 4.
```

PHP Function Parameters

PHP Functions are covered in detail in PHP Function Chapter. In short, a function is a small unit of program which can take some input in the form of parameters and does some processing and may return a value.

Function parameters are declared after the function name and inside parentheses. They are declared much like a typical variable would be:

```
<?
// multiply a value by 10 and return it to the caller
function multiply ($value) {
    $value = $value * 10;
    return $value;
}

$retval = multiply (10);
Print "Return value is $retval\n";
?>
```

This will produce the following result.

```
Return value is 100
```

PHP Global Variables

In contrast to local variables, a global variable can be accessed in any part of the program. However, in order to be modified, a global variable must be explicitly declared to be global in the function in which it is to be modified. This is accomplished, conveniently enough, by placing the keyword **GLOBAL** in front of the variable that should be recognized as global. Placing this keyword in front of an already existing variable tells PHP to use the variable having that name. Consider an example:

```
<?
$somevar = 15;
function addit() {
GLOBAL $somevar;
$somevar++;
print "Somevar is $somevar";
}
addit();
?>
```

This will produce the following result.

```
Somevar is 16
```

PHP Static Variables

The final type of variable scoping that I discuss is known as static. In contrast to the variables declared as function parameters, which are destroyed on the function's exit, a static variable will not lose its value when the function exits and will still hold that value should the function be called again.

You can declare a variable to be static simply by placing the keyword **STATIC** in front of the variable name.

```
<?
function keep_track() {
    STATIC $count = 0;
    $count++;
    print $count;
    print "
";
```

```
}  
keep_track();  
keep_track();  
keep_track();  
?>
```

This will produce the following result.

```
1  
2  
3
```

5.PHP – CONSTANTS

A constant is a name or an identifier for a simple value. A constant value cannot change during the execution of the script. By default, a constant is case-sensitive. By convention, constant identifiers are always uppercase. A constant name starts with a letter or underscore, followed by any number of letters, numbers, or underscores. If you have defined a constant, it can never be changed or undefined.

To define a constant you have to use `define()` function and to retrieve the value of a constant, you have to simply specifying its name. Unlike with variables, you do not need to have a constant with a `$`. You can also use the function `constant()` to read a constant's value if you wish to obtain the constant's name dynamically.

constant() function

As indicated by the name, this function will return the value of the constant.

This is useful when you want to retrieve value of a constant, but you do not know its name, i.e., it is stored in a variable or returned by a function.

constant() example

```
<?php

define("MINSIZE", 50);

echo MINSIZE;
echo constant("MINSIZE"); // same thing as the previous line

?>
```

Only scalar data (boolean, integer, float and string) can be contained in constants.

Differences between constants and variables are

- There is no need to write a dollar sign (\$) before a constant, where as in Variable one has to write a dollar sign.
- Constants cannot be defined by simple assignment, they may only be defined using the `define()` function.
- Constants may be defined and accessed anywhere without regard to variable scoping rules.

- Once the Constants have been set, may not be redefined or undefined.

Valid and invalid constant names

```
// Valid constant names
define("ONE",    "first thing");
define("TWO2",   "second thing");
define("THREE_3", "third thing")
// Invalid constant names
define("2TWO",   "second thing");
define("_THREE_", "third value");
```

PHP Magic constants

PHP provides a large number of predefined constants to any script which it runs.

There are five magical constants that change depending on where they are used. For example, the value of `__LINE__` depends on the line that it's used on in your script. These special constants are case-insensitive and are as follows:

The following table lists a few "magical" PHP constants along with their description:

Name	Description
<code>__LINE__</code>	The current line number of the file.
<code>__FILE__</code>	The full path and filename of the file. If used inside an include, the name of the included file is returned. Since PHP 4.0.2, <code>__FILE__</code> always contains an absolute path whereas in older versions it contained relative path under some circumstances.
<code>__FUNCTION__</code>	The function name. (Added in PHP 4.3.0) As of PHP 5 this constant returns the function name as it was declared (case-sensitive). In PHP 4 its value is always lowercased.
<code>__CLASS__</code>	The class name. (Added in PHP 4.3.0) As of PHP 5 this constant returns the class name as it was declared (case-sensitive). In PHP 4 its value is always lowercased.
<code>__METHOD__</code>	The class method name. (Added in PHP 5.0.0) The method name is returned as it was declared (case-sensitive).

6.PHP – OPERATOR TYPES

What is Operator? Simple answer can be given using expression $4 + 5$ is equal to 9. Here 4 and 5 are called operands and + is called operator. PHP language supports following type of operators.

- Arithmetic Operators
- Comparison Operators
- Logical (or Relational) Operators
- Assignment Operators
- Conditional (or ternary) Operators

Let's have a look on all operators one by one.

Arithmetic Operators

The following arithmetic operators are supported by PHP language:

Assume variable A holds 10 and variable B holds 20 then:

Operator	Description	Example
+	Adds two operands	$A + B$ will give 30
-	Subtracts second operand from the first	$A - B$ will give -10
*	Multiply both operands	$A * B$ will give 200
/	Divide the numerator by denominator	B / A will give 2
%	Modulus Operator and remainder of after an integer division	$B \% A$ will give 0
++	Increment operator, increases integer value by one	A++ will give 11
--	Decrement operator, decreases integer value by one	A-- will give 9

Example

Try the following example to understand all the arithmetic operators. Copy and paste following PHP program in test.php file and keep it in your PHP Server's document root and browse it using any browser.

```
<html>
<head><title>Arithmetical Operators</title></head>
<body>
<?php
    $a = 42;
    $b = 20;

    $c = $a + $b;
    echo "Addition Operation Result: $c <br/>";
    $c = $a - $b;
    echo "Subtraction Operation Result: $c <br/>";
    $c = $a * $b;
    echo "Multiplication Operation Result: $c <br/>";
    $c = $a / $b;
    echo "Division Operation Result: $c <br/>";
    $c = $a % $b;
    echo "Modulus Operation Result: $c <br/>";
    $c = $a++;
    echo "Increment Operation Result: $c <br/>";
    $c = $a--;
    echo "Decrement Operation Result: $c <br/>";
?>
</body>
</html>
```

This will produce the following result:

```
Addition Operation Result: 62
Subtraction Operation Result: 22
Multiplication Operation Result: 840
Division Operation Result: 2.1
```

Modulus Operation Result: 2

Increment Operation Result: 42

Decrement Operation Result: 43

